

Validate

Print

Help

## Percentage BoQ

<b>Tender Inviting Authority: NHIDCL</b>					
<b>Name of Work: Repair and Maintenance of National Highway (NH 52) between Bishwanath Chariali to Gohpur (Km.208.000 to Km. 265.500)(Percentage Rate and Work Order Basis)</b>					
<b>Contract No: NHIDCL/Maint./BC-G/Tender/Tez/2018-19/02</b>					
<b>Bidder Name :</b>					
<b><u>PRICE SCHEDULE</u></b> <b>(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only )</b>					
<b>NUMBER #</b>	<b>TEXT #</b>	<b>TEXT #</b>	<b>NUMBER</b>	<b>NUMBER #</b>	<b>TEXT #</b>
<b>Sl. No.</b>	<b>Item Description</b>	<b>Units</b>	<b>Estimate d Rate</b>	<b>TOTAL AMOUNT Without Taxes</b>	<b>TOTAL AMOUNT In Words</b>
<b>1</b>	<b>2</b>	<b>5</b>	<b>6</b>	<b>53</b>	<b>55</b>
1	<b>Tack coat:</b> Providing and applying tack coat with bitumen emulsion using emulsion pressurre distributor at the rate of 0.20 kg per sqm on the prepared bituminous/ granular surface cleaned with mechanical broom (including cost of testing of materials at site and laboratory as directed by the deptt.) (I) with Bitumen emulsion CSS-1h (a) Normal bituminous surfaceRate Rs./cum including lead	sqm	0.00	Rs. 36,87,250.00	INR Thirty Six Lakh Eighty Seven Thousand Two Hundred & Fifty Only
2	<b>Bituminous Macadam for pothole filling - 50 mm Thickness:</b> 'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled asper Clause 501.60 and 501.7 to achieve the desired compaction.	cum	1.00	Rs. 8,460,858.00	INR Eighty Four Lakh Sixty Thousand Eight Hundred & Fifty Eight Only

	(Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material				
3	<p><b>Bituminous Macadam for overlay - 50 mm Thickness:</b>  Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled as per Clause 501.60 and 501.7 to achieve the desired compaction.  (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	cum	0.00	Rs. 56,405,720.00	INR Five Crore Sixty Four Lakh Five Thousand Seven Hundred & Twenty Only
4	<p><b>Bituminous Concrete- 30 mm thickness:</b>  Providing and laying bituminous concrete with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder@ 5.4 to 5.6 % of mix and filler transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the reqd. grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRT&amp;H cl. no.509. complete in all respect.  (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	cum	0.00	Rs. 47,521,446.00	INR Four Crore Seventy Five Lakh Twenty One Thousand Four Hundred & Forty Six Only
5	<p><b>Road Marking:</b>  Road marking with Hot Applied Thermoplastic Compound with Reflectorising Glass Beads on Bituminous Surface -Providing and laying of Hot applied thermoplastic compound 2.5mm thick</p>	sqm	0.00	Rs. 597,230.40	INR Five Lakh Ninety Seven Thousand Two Hundred & Thirty and

	including reflectorising glass beads @250 gms per sqm, thickness of 2.5mm is exclusive of surface applied glass beads as per IRC:35. the finished surface to be level, uniform and free from streaks and holes.				<b>Paise Forty Only</b>
<b>Total in Figures</b>				<b>Rs. 116,672,504.4 0</b>	<b>INR Eleven Crore Sixty Six Lakh Seventy Two Thousand Five Hundred &amp; Four and Paise Forty Only</b>
<b>Quoted Rate in Figures</b>		<b>Select</b>		<b>0.00</b>	<b>INR Zero Only</b>
<b>Quoted Rate in Words</b>		<b>INR Zero Only</b>			

Validate

Print

Help

## Item Wise BoQ

<b>Tender Inviting Authority: NHIDCL</b>						
<b>Name of Work: Repair and Maintenance of National Highway (NH 52) between Bishwanath Chariali to Gohpur (Km.208.000 to Km. 265.500)(Percentage Rate and Work Order Basis)</b>						
<b>Contract No: NHIDCL/Maint./BC-G/Tender/Tez/2018-19/02</b>						
<b>Bidder Name :</b>						
<b><u>PRICE SCHEDULE</u></b> <b>(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only )</b>						
NUMB ER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	Units	Estimated Rate	TOTAL AMOUNT Without Taxes	TOTAL AMOUNT In Words
1	2	4	5	6	53	55
1	<b>Tack coat:</b> Providing and applying tack coat with bitumen emulsion using emulsion pressurre distributor at the rate of 0.20 kg per sqm on the prepared bituminous/ granular surface cleaned with mechanical broom (including cost of testing of materials at site and laboratory as directed by the deptt.) (I) with Bitumen emulsion CSS-1h (a) Normal bituminous surfaceRate Rs./cum including lead	301000.00	sqm	12.25	<b>Rs.</b> <b>3,687,250.00</b>	INR Thirty Six Lakh Eighty Seven Thousand Two Hundred & Fifty Only

2	<b>Bituminous Macadam for pothole filling - 50 mm Thickness:</b> 'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled as per Clause 501.60 and 501.7 to achieve the desired compaction. (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material	1050.00	cum	8057.96	<b>Rs.</b> <b>8,460,858.00</b>	INR Eighty Four Lakh Sixty Thousand Eight Hundred & Fifty Eight Only
3	<b>Bituminous Macadam for overlay - 50 mm Thickness:</b> 'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled as per Clause 501.60 and 501.7 to achieve the desired compaction. (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material	7000.00	cum	8057.96	<b>Rs.</b> <b>56,405,720.00</b>	INR Five Crore Sixty Four Lakh Five Thousand Seven Hundred & Twenty Only
3	<b>Bituminous Concrete- 30 mm thickness:</b> Providing and laying bituminous concrete with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder@ 5.4 to 5.6 % of mix and filler transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the reqd. grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRT&H cl. no.509. complete in all respect. (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material	4200.000	cum	11314.63	<b>Rs.</b> <b>47,521,446.00</b>	INR Four Crore Seventy Five Lakh Twenty One Thousand Four Hundred & Forty Six Only

4	<b>Road Marking:</b> Road marking with Hot Applied Thermoplastic Compound with Reflectorising Glass Beads on Bituminous Surface -Providing and laying of Hot applied thermoplastic compound 2.5mm thick including reflectorising glass beads @250 gms per sqm, thickness of 2.5mm is exclusive of surface applied glass beads as per IRC:35. the finished surface to be level, uniform and free from streaks and holes.	780.0000	sqm	765.68	<b>Rs.</b> <b>597,230.40</b>	INR Five Lakh Ninety Seven Thousand Two Hundred & Thirty and Paise Forty Only
<b>Total in Figures</b>					<b>Rs.</b> <b>116,672,50</b> <b>4.40</b>	INR Eleven Crore Sixty Six Lakh Seventy Two Thousand Five Hundred & Four and Paise Forty Only
<b>Quoted Rate in Words</b>		<b>INR Eleven Crore Sixty Six Lakh Seventy Two  Thousand Five Hundred &amp; Four and Paise Forty  Only</b>				